

LITEX, INC.
5985 NW 31st Avenue, Ft. Lauderdale, FL 33309
(954) 970-0361 (954) 974-7524 fax

<u>HMS HAZARD RATINGS</u>	
Health Hazard	0
Flammability Hazard	0
Reactivity Hazard	0
Maximum Personal Protection	n/a

MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT IDENTIFICATION

PRODUCT TRADE NAME: **POPCORN CEILING PATCH & REPAIR (ITEM #5001 & 5004)**
SHIPPING NAME: Litex, Inc. DOT HAZARD CLASSIFICATION: Not restricted
TECHNICAL CONTACT NAME: Gene O'Neill
FORMULA/MOLECULAR STRUCTURE n/a
CHEMICAL NAME/SYNONYMS: MATERIAL CAN CONTAIN: Aqueous mixtures of clays, hydroxypropyl, calcium, methyl cellulose, ethyl vinyl, acetate adhesive and styrofoam.

SECTION II - PRODUCT DESCRIPTION

APPEARANCE: White paste ODOR: Neutral
PHYSICAL DATA: Density 11 lbs./gallon - Percent volatiles at 70°F none
HAZARDOUS COMPONENTS: This product is not manufactured to contain components which are deemed in hazardous proportions.

SECTION III - FIRE AND EXPLOSION DATA

FLASH POINT/F: n/a TEST METHOD: n/a
RECOMMENDED EXTINGUISHING MEDIA: ☒ Water ☒ CO2 ☒ Foam ☒ Other Dry Chemicals
UNUSUAL FIRE OR EXPLOSION HAZARDS
(conditions to avoid): Product is slippery when spilled.
SPECIAL FIRE FIGHTING PROCEDURES: None known

SECTION IV - REACTIVITY DATA

STABILITY UNDER NORMAL CONDITIONS: ☒ Stable ☐ Unstable (conditions to avoid:)
INCOMPATIBLE MATERIALS
(materials to avoid): ☐ Water ☐ Acid ☐ Base ☐ Oxidizers ☐ Other ☒ None Known
HAZARDOUS POLYMERIZATION: ☒ Will Not Occur ☐ May Occur (conditions to avoid:)

SECTION V - ACUTE HEALTH AND SAFETY DATA

TEST TYPE: None Conducted
RESULT:
HAZARD DESCRIPTION:

SECTION VI - HANDLING PRECAUTIONS/FIRST AID RECOMMENDATIONS

SKIN & EYE CONTACT: Wash with water. Product is considered to be non-irritating to eyes and skin based on quantities of ingredients in the product. If splashed in the eye, flush with copious quantities of water and seek medical attention.

ORAL INGESTION: Considered to be non-toxic based on toxicological data for components. If swallowed in large quantities, seek medical attention.

SECTION VII - SPILL PROCEDURES

STEPS TO TAKE IF SPILLED: Spilled material is slippery. Use care to avoid falls. Pick up spilled material and hose or mop down area.

WASTE DISPOSAL: This product is not considered hazardous waste. Dispose of in an approved landfill in accordance with state and local regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

VENTILATION REQUIREMENTS: ☐ General Area Exhaust ☐ Local Exhaust ☒ Not Necessary Under Normal Use Conditions

PERSONAL PROTECTION EQUIPMENT RECOMMENDED FOR NORMAL USE CONDITIONS:

☐ Eye ☐ Skin ☐ Respiration

SECTION IX - SPECIAL PRECAUTIONS

Product is slippery when spilled.

THE INFORMATION HEREIN RELATES TO THE PRODUCT NAMED AND IS BASED UPON INFORMATION CONSIDERED TO BE ACCURATE. NO WARRANTY, EXPRESSED OR IMPLIED, IS INTENDED. THIS INFORMATION IS OFFERED SOLELY FOR YOUR CONSIDERATION AND INTERPRETATION.

LITEX, INC., 5985 NW 31st Avenue, Fort Lauderdale, Florida 33309
LITEX, INC., 3630 E. Wawona Avenue #102, Fresno, CA 93725

SPEC SHEET
ITEM #5001 & 5004
Popcorn Patch & Repair

SPECIFICATION: Product will meet or exceed the performance of Federal Specification numbers SS-P-450 Type II.

WEIGHT PER

GALLON: 6.6 plus/minus .2 pounds
Conforms to ASTM D1475

VISCOSITY: >140 K.U.'s

GLOSS: N/A

FINENESS OF

GRIND: N/A

DRY TIME: To touch: 2 hours
Dry hard: 48 hours
Conforms to ASTM D1640

PH: 8.5-9.5

CAS Number:

7732-18-5	Water
Proprietary	Vinyl Acrylic
00471-34-1	Calcium Carbonate
12269-78-2	Pyrophyllite
93763-70-3	Silicate